

# AGRITEC CHAINSAW 100XT

Product Code: AGR011 | Revision: 20220322



Premium anti-fling cutter bar lubricant for chainsaws.

### Available Pack Sizes



### Applications

A premium tenacious & tacky lubricant developed for the lubrication of chainsaw cutter bars. Incorporating advanced surface active agents to ensure maximum penetration of the chain to reduce wear, provide corrosion protection and resist the tendency to fling during operation.

### Recommended by Aztec Oils as suitable for the following applications

Primarily for the lubrication of cutter bars and chains of pump & pressure-fed chainsaws requiring an ISO 100 or SAE 30 lubricant.

### Benefits

- Advanced EP & tackiness properties.
- Improves chain life.
- Protects against corrosion.
- Resistant against oil fling.

### Typical Test Data

Density @ 15°C (kg/m3)	ASTM D4052	0.88
Flash Point (°C)	ASTM D92	>200
Kinematic Viscosity @ 40°C (mm/s <sup>2</sup> )	ASTM D445	100
Kinematic Viscosity @ 100°C (mm/s <sup>2</sup> )	ASTM D445	11.3
Pour Point (°C)	ASTM D97	-10
Viscosity Index	ASTM D2207	99

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.